

ZINK-GRO™ 15

13-0-0

PRODUCT SPECIFICATIONS

TYPICAL PHYSICAL PROPERTIES

Screen Analysis.....97% Between 2 - 4.2 mm
 Color.....White to Light Gray
 pH.....8.0 - 8.5
 Hardness.....6.0 lbs / Granule
 Bulk Density.....48 lbs. per cu. foot
 SGN (Size Guide Number).....280
 Granulation.....Prilled

TYPICAL CHEMICAL ANALYSIS

Derived from Ulexite
 Typical Analysis.....Boron (B) 14.3 to 15.0%
 GUARANTEED Analysis.....Boron (B) 14.3%
 Equivalent B2O3.....46.0 - 48.3%
 Arsenic (As).....< 100 ppm
 Cadmium (Cd).....< 2 ppm
 Cobalt (Co).....< 3 ppm
 Lead (Pb).....< 5 ppm
 Mercury (Hg).....< 0.1 ppm
 Molybdenum (Mo).....< 10 ppm
 Nickel (Ni).....< 3 ppm
 Selenium (Se).....< 1 ppm

PACKAGING OPTIONS

- Multi-ply 50 lb. Bags with PE Liner (40 bags per ton pallet)
- 1500 lb. Polypropylene Super Bags (1 per pallet)

SHIPPING POINTS

Fairbury, Nebraska
 * Gulf Coast Warehouse
 * Pacific Northwest Warehouse
 * Northern U.S. Warehouse
 * Call for exact locations

15% BORON FORMULATION GUIDE

Lbs./Acre of B Required	1	2	3	4	5	6
LBS. OF 15% TETRA-BOR	6.7	13.4	20.1	26.7	33.4	40.0